

MIN 2500~6000 TL-XE

- Maximum efficiency 98.4%
- Dual MPP trackers
- Type II SPD on DC side
- Supports export control
- Touch key and OLED display



Growatt
powering tomorrow



www.ginverter.com

P O W E R
- I N G
T O M O -
R R O W

Input Data

Output (AC)

Rated AC output power	2500W	3000W	3600W	4200W	4600W	5000W	6000W
Max. AC apparent power	2500VA	3000VA	3600VA	4200VA	4600VA	5000VA	6000VA

Efficiency

Max. efficiency	98.2%	98.2%	98.2%	98.4%	98.4%	98.4%	98.4%
Euro-weighted efficiency	97.1%	97.1%	97.0%	97.5%	97.5%	97.5%	97.6%

Protection Devices

DC reverse polarity protection	yes	yes	yes	yes	yes	yes	yes
DC switch	yes	yes	yes	yes	yes	yes	yes

General Data

Dimensions (W / H / D) in mm	375/350/160	375/350/160	375/350/160	375/350/160	375/350/160	375/350/160	375/350/160
Weight	10.8KG	10.8KG	10.8KG	10.8KG	10.8KG	10.8KG	10.8KG

Features

DC connection	H4/MC4(opt)	H4/MC4(opt)	H4/MC4(opt)	H4/MC4(opt)	H4/MC4(opt)	H4/MC4(opt)	H4/MC4(opt)
1	2	3	4	5	6	7	8

CE, IEC62109, G98, G99, VER2014, CFI0-21, VDE-AR-N4105, EN50549, IEC61727, IEC62116